ECO-WEAVED GRATE RANGE R&S Since 1974 Contact in the same of the s



Fully compliant to AS3996 - 2006 bicycle tyre penetration resistance (BTPR) requirements, the Eco-Weaved sump grate range is ideal for areas anticipated to experience both vehicle and bicycle traffic.



Utilising strong M12 bolts, the Eco-Weaved sump grate range is bolted down, standard. In addition to preventing tampering, the bolt down system prevents rocking and dislodgement, fully securing the grate to the ground.



All Eco-Weaved grates are manufactured to heavy duty (Class D) of AS3996 requirements. The load-sharing weaved design, coupled with high strength steel, facilitates a highly efficient distribution of load.

- **✓** LIGHTER
- **✓** STRONGER
- **✓** SAFER







FLAT

"V" STYLE

Product Code

ISG-W90375SM2 ISG-W9035GAA

CONVERTED SIDE ENTRY

-M	SG-H	900 x 375	EDCM604	gure 13	Fi	Sm2 / "V"
٥V	SG-H	900 x 350	EDCM601	gure 12	Fi	Flat
		15 / K / G				
	Code	"V" Product	oduct Code	Flat Pr	Pit Size (mm)	
	V4545	SG-H-MSG-EW	SG-EW4545	SG-H-M	0	450 x 450
	V6060	SG-H-MSG-EW	SG-EW6060	SG-H-M	0	600 x 600
	V7575	SG-H-MSG-EW	SG-EW7575	SG-H-M	0	750 x 750
	V9045	SG-H-MSG-EW	SG-EW9045	SG-H-M	0	900 x 450
	V9060	SG-H-MSG-EW	SG-EW9060	SG-H-M	0	900 x 600
	V9090	SG-H-MSG-EW	SG-EW9090	SG-H-M	0	900 x 900
		SG-H-MSG-EW	SG-EW9090	SG-H-M	ט	900 X 900

Converted Side Entry (900 x 600mm Pit Size)				
Bullnose	SG-H-MSG-CSE-EW9060B			
Rollover	SG-H-MSG-CSE-EW9060			

Learn more: grating.com.au/eco-weaved

